

# ISUZU NOVOciti



**EURO**



Anadolu Isuzu the one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

**ANADOLU ISUZU**

# ISUZU NOVOcITI



Anadolu Isuzu's solid medium size coach is also available with a Class 1 version for inner-city public transportation. Novociti is a result of nearly 35 years of design and manufacturing experience of Anadolu Isuzu and it is powered by world-famous Isuzu engine which produces 190 PS at 2600 RPM. Novociti provides sufficient traction power for inner-city use with its 510 NM torque rate between 1600 – 2600 rpm. Thanks to its compact size and smart design, Novociti provides an easy drive even in the narrowest streets of the old metropolises. The spacious interior design gives enough space for up to 55 passengers on transit lines.



EURO



ANADOLU ISUZU

# ISUZU NOVOcITI

## TECHNICAL SPECIFICATIONS

Dimensions (mm)	
Maximum Length	7505
Maximum Width	2275
Maximum Height	3375 (Inc. A/C)
Wheelbase	3385
Front Overhang	1695
Rear Overhang	2462
Front Track Width	1914
Rear Track Width	1650
Inner Height	2170
Weights (kg)	
Gross Vehicle Weight	9800
Engine	
Model	ISUZU 4HK1E5N (Euro 5-EEV)
Type	Commonrail Turbo Diesel Intercooler
Cylinders	4
Displacement (cc)	5193
Maximum Power (PS/rpm)	155 / 2600
Maximum Torque (Nm/rpm (Kgm/rpm))	419 /1600-2600 (42,7 /1600-2600)
Transmission	
Model	MYT
Number of Gears, Type	6 forward, 1 reverse, Manual, Overdrive
Steering System	Hydraulic, Tilt and Telescopic
Tyres	215/75 R17,5
Suspensions	
Front	Parabolic Steel Alloy Leaf Springs
Rear	Air Suspension
Brake System	
Front / Rear	Disc / Disc
System	Full Air Brake System with ABS, Dual Circuit, Auto-adjusted
Parking Brake	Air Actuated, Operating on Rear Axle
Auxiliary Brake	Vacuum Assisted Exhaust Brake (S) Retarder (Opt), Bus Stop Brake (Opt)
Fuel Tank	
Fuel Tank Capacity (lt)	130
Electrical System	
Battery	24V (2X12V)-105 Ah
Passenger Capacity	
2 Door Version	16 (Seated) + 39 (Standing) 16 (Seated) + 34 (Standing) + 1 (Wheelchair) 21 (Seated) + 33 (Standing) 21 (Seated) + 25 (Standing) + 1 (Wheelchair)
Folding Seats	4 Seats (Opt)



Novociti offers a safe and comfortable journey for its passengers and the driver. In order to maximize the comfort of driver, Novociti is designed with an ergonomic dashboard with a driver-friendly instrument panel, hydraulic power steering, a shelf above the driver seat for his/her private use and timer-adjusted heated driver window. ABS, disc brakes, retarder and rear air suspension are among other equipments which assure a safe and comfortable trip for the passengers.

# ISUZU NOVOcITI

## EQUIPMENTS



### Heating and Ventilation

Pre-heater	Opt
Air-blowing Type Heater (Front)	S

### Air Conditioner

A/C Dashboard Unit For Driver	S
-------------------------------	---

### Safety & Driving Comfort

Speed Limitor	S
Tachograph	Digital Tachograph (S) / MTCO (Opt)
Retarder	Opt
ABS	S
ASR	S
Rear view camera	Opt
Parking Sensor	Opt
Roof Emergency Exit & Ventilation Hatch	S
Immobiliser	S
Reverse Gear Warning Beeper	S

### EXTERIOR

Metallic Colour	Opt
Towing Hook	S

### Doors

Front Door	Double Wings, Pneumatic, Outward Swing
Rear	Double Wings, Pneumatic, Outward Swing, Auto-locking System Over 5 km/h Speed (Opt)
Remote Control	S
Wheelchair / Strollers Ramp	S (Rear Door)

### INTERIOR

#### Driver Seat

Driver's Seat	Ergonomic, Air Operated, Adjustable
Lamp For Driver Seat	S
Driver's Window	Manuel Sliding, Anti-mist Heater
Front Door Window	Anti-mist Heater
Windscreen Blind	S (Electrically Controlled Optional)
Electrically Controlled Mirrors	Opt
Close-proximity Exterior Mirror	S

#### Passenger Compartment

Passenger Seat Material	Fabric
Ceiling Material	Formica and ABS
Side Wall Lining Material	Formica
Floor Covering	Vinyl

#### Lightening & Signalization

Interior Lighting (Ceiling)	Continuous on Ceiling
Stop Sign & Buttons	S
Digital Destination Line Indicator	S
Destination Line Board (Middle)	S

#### Audio & Visual

Radio & CD Player	S
Monitor / LCD	Opt
Digital Clock	S

S: Standard Opt: Optional