ISUZU CITIBUS

Genel



Anadolu Isuzu the one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

ANADOLU ISUZU



0

Ś i

Genel

ISUZU

0

CITIBUS

isuzu

Anadolu Isuzu's 9,5 meter public transportation bus is designed to meet the requirements of old metropolises with narrow streets and for those smaller municipialities which have to serve in several transit routes including urban areas with lower populations. Today, on the other hand, most of the larger municipialities have also begun to invest on smaller buses as an economical option for their regular transit routes.

ISUZU CITIBUS





Genel

TECHNICAL SPECIFICATIONS	
Dimensions (mm)	
Maximum Length	9515
Maximum Length Maximum Width	2409
Maximum Width Maximum Height	3117 (with A/C unit)
Wheelbase	4435
Front Overhang	2135
ē	2155
Rear Overhang	2943
Weights (kg)	
Gross Vehicle Weight	14000
Front Axle Capacity	5000
Rear Axle Capacity	9440
Engine	
Model	ISUZU 4HK1E2S
Туре	Commonrail Turbo Diesel Intercooler
Cylinders	4
Displacement (cc)	5193
Maximum Power (PS/rpm)	210 / 2600
Maximum Torque (Nm/rpm)	637 /1600-2600
Clutch	Hydraulic Actuated With Diaphram
Cluten	Spring and Single Dry Plate
Transmission	
	ISUZU MZW (E Monuel (S)
Model	ISUZU MZW-6F Manual (S)
	ALLISON 2100 Automatic (Opt)
	6 Forward, 1 Reverse, Overdrive (S)
Number of Gears, Type	5 Forward, 1 Reverse (Opt)
Steering System	Hydraulic, Tilt and Telescopic
Tyres	265/70 R19.5
•	203/70 R19,5
Suspensions	
Front	Air Suspension - 2 Air Bellows
	Independent Suspension
Rear	Air Suspension - 4 Air Bellows
Kneeling System	S
Brake System	
Front / Rear	Disc / Disc
Stratom	Full Air Brake System with ABS, Dual
System	Circuit, Auto-adjusted
Parking Brake	Air Actuated, Operating on Rear Axle
Auxiliary Brake	Exhaust Brake (S), Retarder (Opt),
	Bus Stop Brake (Opt)
Fuel Tank	
Fuel Tank Capacity (lt)	215
Passenger Capacity	
	17 Seated + 57 Standing
3 Door Version	17 Seated + 30 Standing + 1 Wheelchain
	18 Seated + 58 Standing
2 Door Version	
	18 Seated + 51 Standing + 1 Wheelchair
Folding Seats	2 Seats (Opt)
-	



Isuzu engine in Citibus produces 210 PS and the bus has Isuzu manual transmission, also optional Allison 2100 automatic transmission. Spacious interior layout, kneeling system and an easy-to-use wheelchair ramp enhance the accessibility of the vehicle and allows a barrier-free journey for all passengers. ABS, ASR, integrated optional retarder, independent air suspension and optional integrated CCTV system allow a safe ride for the driver and the passengers in intense city traffic.

ISUZU CITIBUS

Genel



Opt S g Type Heater On Right Side (Opt) Controlled Air Conditioner S gital Tachograph (S) Dpt (Pedal Control) S S Opt
S g Type Heater On Right Side (Opt) Controlled Air Conditioner S gital Tachograph (S) Dpt (Pedal Control) S S
S g Type Heater On Right Side (Opt) Controlled Air Conditioner S gital Tachograph (S) Dpt (Pedal Control) S S
(Opt) Controlled Air Conditioner S gital Tachograph (S) Opt (Pedal Control) S S
Controlled Air Conditioner S gital Tachograph (S) Dpt (Pedal Control) S S
S gital Tachograph (S) Dpt (Pedal Control) S S
gital Tachograph (S) Dpt (Pedal Control) S S
gital Tachograph (S) Dpt (Pedal Control) S S
Dpt (Pedal Control) S S
S S
S
Opt
Opt S
S
S
Opt
S
que, Cataphoresis Coating
Opt
iding Window On Each Side
S
S
bors (S), 2 Doors (Opt)
ng, Pneumatic, Inward Swing
ngs, Pneumatic, Inward Swing
ng, Pneumatic, Inward Swing S
S (Middle Door)
b (Middle Boor)
Opt
ic, Air Operated, Adjustable
S
Sliding, Anti-mist Heater
Double Glazing
S (Manual)
Opt S
S
ic With Fabric Coating
Formica
Formica Formica
Formica
Formica Vinyl inuous LED on Ceiling
Formica Vinyl inuous LED on Ceiling S
Formica Vinyl inuous LED on Ceiling S (Rounding Header)
Formica Vinyl inuous LED on Ceiling S (Rounding Header) S
Formica Vinyl inuous LED on Ceiling S (Rounding Header)
Formica Vinyl inuous LED on Ceiling S (Rounding Header) S Opt
Formica Vinyl inuous LED on Ceiling S (Rounding Header) S Opt Opt
Formica Vinyl inuous LED on Ceiling S (Rounding Header) S Opt
Formica Vinyl inuous LED on Ceiling S (Rounding Header) S Opt Opt Opt Opt

S: Standard Opt: Optional



