



CITIBUS

Manufactured by Anadolu Isuzu

The one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

TECHNICAL SPECIFICATIONS

Dimensions (mm)

Maximum Length	9515
Maximum Width	2409
Maximum Height	3117 (w A/C)
Wheelbase	4435
Front Overhang	2135
Rear Overhang	2945

Weights (kg)

Gross Vehicle Weight	13500
----------------------	-------

Engine

Model	Cummins B4.5E6E210B
Type	Commonrail Turbo Diesel Intercooler
Number of Cylinders	4
Displacement (cc)	4500
Maximum Power (kw(PS)/rpm)	151 (205) / 2300
Maximum Torque (Nm/rpm)	832 /1200-1450
Emission Standard	Euro VI OBD-E

Transmission

Model	Allison T 280 R
Number of Gears	6 Forward, 1 Reverse

Steering System

Tyres	Hydraulic
-------	-----------

Tyres

Tyre Sizes	265/70 R19,5
------------	--------------

Suspension

Front	Independent Air Suspension - 2 Air Bellows
Rear	Air suspension - 4 bellows electronically controlled

Anti Roll Bar	S
Kneeling System (ECAS & ELC)	S

Brake System

Front / Rear System	Disc / Disc Full Air Brake System with EBS and ABS, Dual Circuit, Auto-Adjusted
Parking Brake	Air Actuated Acted on the Rear Axle
Auxiliary Brake	Retarder

Fuel Tank

Fuel Tank Capacity (lt)	215
Adblue Tank (lt)	30

Electrical System

Battery	24V (2X12V) - 150 Ah
---------	----------------------

Passenger Capacity*

Maximum Passenger Capacity	76
Optional Seat Layouts	18 Seated + 58 Standing (2 Doors)
Standard Layout	25 Seated (3 Foldable Seats) + 44 Standing (3 Doors)
Standard Layout with Wheelchair	22 Seated + 1 Wheelchair + 43 Standing (3 Doors)

EQUIPMENTS

Heating and Ventilation

Pre Heater	Opt
Fan Heater (Front/Middle/Rear)	S

Air Conditioner

Digital Air Conditioner	S
A/C Dashboard Nozzle Diffuser for Driver	S
Tropical A/C	Opt

Safety & Driving Comfort

Tachograph	S
ABS	S
ASR	S
EBS	S
EBD	S
Bus Stop Brake (BSB)	S
Hillholder	S
Retarder	S
Parking Sensor	Opt
Spare Wheel	S
Tyre Inflation Set	S
Roof Hatch for Ventilation & Emergency Exit	S
Reverse Gear Warning Beeper	S
Fire Extinguisher	S
Engine Compartment Fire Detection and Automatic Fire Suppression System	S
Fog Lamps	S (Front / Rear)
Locking System	S
Battery Main Switch	S

Exterior

Metallic Paint	Opt
Towing Device	S

Doors

Number of Service Doors	3 Doors (S), 2 Doors (Opt)
Type of Service Doors	Front: Single Wing Air Power Actuated Inside Opening Mechanism Middle: Double Wing Air Power Actuated Inside Opening Mechanism Rear: Single Wing Air Power Actuated Inside Opening Mechanism (3 doors) S (Middle Door With Sensor) Opt
Wheelchair / Strollers Ramp	
Remote Control	

Windows

Passenger Windows	One Piece 1/3 Sliding Window on Each Side, Single Glazed (S), Double Glazed (Opt)
Front Door Window	Double Glazed (S)
Driver's Window	Sliding, Single Glazed With Heater (S)
Blind	Windshield Blind (S), Driver Curtain (Opt)

Interior

Driver Seat

Driver's Seat	Ergonomic, Air Operated, Adjustable
Electrically Controlled and Heated Side Mirrors	Heated (S), Electrically Controlled (Opt)
Ticket Validator Preparation	Opt
USB Charger for Driver	S

Passenger Compartment

Backrest (for Standing Passengers)	S
USB Charger for Passengers	Opt

Lightening & Signalization

Interior Ceiling Lighting	S
Stop Buttons & Signboard	S
Digital Destination Display	Front, Rear (S), Colored (Opt)

Audio & Visual

Camera Systems	Opt
Camera Monitor on Dashboard	Opt
Recording Device (DVR)	Opt
Radio System	Radio, USB, MP3
Monitor / LCD Screen (Passenger Compartment)	Opt
Digital Clock	Opt
Driver Speaker	S
Announcement System for Passenger Area	Opt

S: Standard Opt: Optional

* Different seating variations are available.

