



CITIBUS

Manufactured by Anadolu Isuzu

The one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

TECHNICAL SPECIFICATIONS

Dimensions (mm)

Maximum Length	9515
Maximum Width	2409
Maximum Height	3117 (w A/C)
Wheelbase	4435
Front Overhang	2135
Rear Overhang	2945

Weights (kg)

Gross Vehicle Weight	13500
----------------------	-------

Engine

Model	CUMMINS B4.5E6D210B
Type	Commonrail Turbo Diesel Intercooler
Number of Cylinders	4
Displacement (cc)	4500
Maximum Power (kw(HP)/rpm)	157 (211) / 2300
Maximum Torque (Nm/rpm)	850 /1200-1500
Emission Standard	Euro VI OBD-D

Transmission

Model	AT: Allison T 280 R
Number of Gears	6 Forward, 1 Reverse; Overdrive

Steering System

	Hydraulic
--	-----------

Tyres

Tyre Sizes	265/70 R19,5
------------	--------------

Suspension

Front	Independent Air Suspension - 2 Air Bellows
Rear	Air Suspension - 4 Air Springs
Anti Roll Bar	S
Kneeling System	S (ECAS)

Brake System

Front / Rear System	Disc / Disc Full Air Brake System with EBS and ABS, Dual Circuit, Auto-Adjusted Air Actuated Acted on the Rear Axle Retarder
Parking Brake	
Auxiliary Brake	

Fuel Tank

Fuel Tank Capacity (lt)	215
Adblue Tank (lt)	30

Electrical System

Battery	24V (2X12V) - 150 Ah
---------	----------------------

Passenger Capacity*

Maximum Passenger Capacity	76 Passengers
Standard Layout	25 Seated (1 Foldable) + 43 Standing (3 Doors) 25 Seated + 47 Standing (2 Doors)

EQUIPMENTS

Heating and Ventilation

Pre Heater	Opt
Fan Heater	S (front, middle and rear)

Air Conditioner

Digital Air Conditioner	S
A/C Dashboard Nozzle Diffuser for Driver	S
Tropical A/C	Opt

Safety & Driving Comfort

Speed Limitor	Opt
Tachograph	S
ABS	S
ASR	S
EBS	S
Bus Stop Brake (BSB)	S
Retarder	S
Spare Wheel	S
Roof Hatch for Ventilation & Emergency Exit	S
Reverse Gear Warning Beeper	S
Fire Extinguisher	S
Engine Compartment Fire Detection System	S
Engine Compartment Fire Detection and Automatic Fire Suppression System	Opt
Fog Lamps	S (Front and Rear)
Rear View Camera	Opt
Front View Camera	Opt
Interior Camera	Opt

Exterior

Metallic Paint	Opt
Towing Device	S (Front)

Doors

Number of Service Doors	3 Doors (S), 2 Doors (Opt)
Type of Service Doors	Front: Single Wing Air Power Actuated Inside Opening Mechanism Middle: Double Wing Air Power Actuated Inside Opening Mechanism Rear: Single Wing Air Power Actuated Inside Opening Mechanism (3 doors) S (Middle Door With Sensor)
Wheelchair / Strollers Ramp	
Remote Control	S

Windows

Passenger Windows	One Piece 1/3 Sliding Window on Each Side, Single Glazed (S) Double Glazed (Opt) Double Glazed (S) Sliding, Single Glazed With Heater (S) Windshield Blind (S), Driver Curtain (Opt)
Front Door Window	
Driver's Window	
Blind	

Interior

Driver Seat

Driver's Seat	Ergonomic, Air Operated, Adjustable
Electrically Controlled and Heated Side Mirrors	Heated (S), Electrically Controlled (Opt)
Ticket Validator Preperation	Opt
USB Charger for Driver	S

Passenger Compartment

Backrest (for Standing Passengers)	S
USB Charger for Passengers	Opt

Lightening & Signalization

Interior Ceiling Lighting	S (Continuous Type With LED)
Digital Destination Display	Slither Route Display (S), Rear Route Indicator Panel (S), Colored Front Route Indicator Panel (Opt)

Audio & Visual

Radio & MP3	Radio (S), MP3 (Opt)
DVD	Opt
Monitor / LCD Screen (Passenger Compartment)	Opt (Front, Side, Rear)
Digital Clock	S

S: Standard Opt: Optional

* Different seating variations are available.

